

## WEA403i



Radio Specifications	802.11a/b/g/n/ac Dual concurrent radio 3 x 3 MIMO, 3 spatial streams PHY data rates up to 1.3 Gbps Dynamic frequency selection (DFS) 802.11n high throughput (HT20/40) 802.11ac high throughput (HT20/40/80)						
Operation Mode	Controlled Mode, Stand-alone Mode						
Supported Wireless LAN Controller	WEC8500 Series WEC8050 Series						
RF Monitoring	Dedicated RF and security monitoring module in AP						
Data Rates	802.11a : 6,9,12,18,24,36,48 and 54 Mbps 802.11g : 1, 2, 5.5, 6, 9, 11, 12, 18, 24, 36, 48 and 54 Mbps 802.11n : MCS 0 to MCS 23 (6.5 Mbps ~450 Mbps) 802.11ac : MCS 0 to MCS 9 (6.5 Mbps ~ 1.3Gbps)						
Frequency Band	802.11b/g/n : 2.412 GHz ~ 2.472 GHz 13 CH 802.11a/n/ac : 5.180 GHz ~ 5.825 GHz 24 CH * Available channel is compliant with local domain regulatory						
Maximum Transmit Power	23 dBm @ 3 streams (5 ~ 23 dBm) * The maximum transmit power will vary by channel and according to individual country regulation						
Receive Sensitivity	Rate	2.4 GHz			5 GHz		
		HT20	HT40		VHT20	VHT40	VHT80
	MCS 0	-91	-93	-90			
	MCS 7	-71	-73	-70			
	MCS 8	-88	-90	-87			
	MCS 15	-68	-70	-67			
	MCS 16	-86	-88	-85			
	MCS 23	-66	-68	-65			
	MCS 0/NSS1				-93	-90	-86
	MCS 7/NSS1				-73	-70	-67
	MCS 8/NSS1				-68	-66	-63
	MCS 9/NSS1				NA	-64	-61
	MCS 0/NSS2				-90	-87	-83
	MCS 7/NSS2				-70	-67	-64
	MCS 8/NSS2				-65	-63	-60
	MCS 9/NSS2				NA	-61	-58
	MCS 0/NSS3				-88	-85	-82
	MCS 7/NSS3				-68	-65	-62
	MCS 8/NSS3				-64	-61	-58
	MCS 9/NSS3				-62	-59	-56
802.11 b							
	1 Mbps	-96					
	11 Mbps	-88					
802.11 a/g							
	6 Mbps	-93	-93				
	54 Mbps	-74	-75				

## WEA403i



Integrated Antenna	Intelligent Beam Selectable Antenna (IBSA) 2.4 GHz : 3.0 dBi 5 GHz : 5.5 dBi
Antenna Type	Internal Type
Interfaces	2 * 10/100/1000BASE-T (PoE 1 port) 1 * Console interface
Dimensions	Diameter x Height: 205 x 45 (mm)
Weight	860g
Environmental	Storage temperature : -25°C~ +70°C Operating temperature : 0°C~ +45°C Operating humidity : 0~90% (noncondensing)
Input Power Requirements	IEEE 802.3at PoE : 50 to 57 VDC
Powering Options	Local power supply : 48V/0.75A
Power Draw	19.3W
Compliance Standards	<ul style="list-style-type: none"> <li>• Safety : <ul style="list-style-type: none"> <li>UL 60950-1</li> <li>UL 2043</li> <li>IEC 60950-1</li> <li>EN 60950-1</li> <li>EMI and susceptibility (Class B)</li> <li>FCC Part 15.107 and 15.109</li> <li>EN 301 489-1 and -17 (Europe)</li> <li>KN 301 489-1/KN 301 489-17 (Korea)</li> </ul> </li> <li>• Radio approvals : <ul style="list-style-type: none"> <li>FCC Part 15.247, 15.407</li> <li>EN 300 328, EN 301 893(Europe)</li> <li>Radio Equipment Specifications (Korea)</li> </ul> </li> <li>• EAP type (s) : <ul style="list-style-type: none"> <li>Extensible Authentication Protocol - Transport Layer Security (EAP-TLS)</li> <li>EAP-Tunneled TLS (TTLS) or Microsoft Challenge Handshake Authentication Protocol Version 2 (MSCHAPv2)</li> <li>Protected EAP (PEAP) v0 or EAP - MSCHAPv2</li> <li>Extensible Authentication Protocol - Flexible Authentication via Secure Tunneling (EAP-FAST)</li> <li>PEAPv1 or EAP-Generic Token Card (GTC)</li> <li>EAP-Subscriber Identity Module (SIM)</li> </ul> </li> <li>• Multimedia : <ul style="list-style-type: none"> <li>Wi-Fi Multimedia (WMM)</li> <li>WMM-PS</li> </ul> </li> </ul>
Part Number	<ul style="list-style-type: none"> <li>• AP type</li> <li>WDS-A403i / KOR, / XAR, / EUS</li> <li>• Mounting kit</li> <li>WDS-300CK / KOR, / XAR, / EUS : Ceiling mounting kit</li> </ul>